

SPEC for A-274	
Center Frequency:	152 MHz
Band Width:	2MHz
Gain:	6dB
Power Input:	150 Watts Max.
Impedances:	50 Ohms
VSWR:	1.3 : 1
Connector Type:	N - Female
Dimensions:	4750mm (H) x Ø38 to a taper of 13mm Metal Cap at Tip
Colour:	White Radome
Constrution:	Coaxial Dipole Design Fiberglass Radome Brass Cap 306 Stainless Mounting Base DC Grounded Internally

Note:

- 1/ Mount to an elevated pole using 2 U clamps around stainless steel base section.
- 2/ Ensure mounting pole does not extend past top stainless base.
- 3/ Mounting hardware not supplied.

See Notes


Ø38x400(L)
STAINLESS STEEL

4750 MAX.

THIS DOCUMENT AND THE DESIGN SHOWN THEREON IS THE PROPERTY OF ROJONE PTY LTD AND MUST NOT BE SOLD, LENT, GIVEN AWAY, COPIED, REPRODUCED OR OTHERWISE DIVULGED TO ANY THIRD PARTY OR USED FOR MANUFACTURE. DO NOT SCALE OR ANY OTHER PURPOSE WITHOUT DIRECT WRITTEN PERMISSION OF ROJONE PTY LTD.

3rd ANGLE PROJECTION

REVISIONS				
ISS	ZONE	DESCRIPTION/PER REQUEST	DATE	CHECK
A		FIRST ISSUE	20110825	


ROJONE PTY LTD ACN 002691241
 44 AERO RD INGLEBURN 2565
 SYDNEY, AUSTRALIA
 Ph: (612) 9829 1555 Fax: (612) 9605 8812
 Web: www.rojone.com.au E-mail: sales@rojone.com.au

TITLE		VHF 6dB COLINEAR BASESTATION ANT A-274	
DRAWN		Y. GU	
CHECKED		H. JIA	
APPROVED		B. G.	
DRWG No:	009001001311		
SCALE	NTS	SHEET	1 OF 1
FILENAME	009001001311ISSB.DWG		

A4