



SPEC for AMA-3121

Frequency:	902 - 928 MHz
Gain:	18 dB Typ
DC Supply:	100 mA / 9-15 V
OIP3 of LNA:	> 30 dBm
NF of LNA:	1.2 dB Typ
Size:	67 x 43 x 15 mm
Op Temp:	-30 to + 60 °C
Humidity:	100 %
RF Conn:	SMA-F & SMB-F +Conn.
Weight:	150 g

Note: LNA with automatic level control (ALC).

REVISIONS		
ISS	ZONE	DESCRIPTION/PER REQUEST/DATE
b		Updated spec

3rd ANGLE PROJECTION

THIS DOCUMENT AND THE DESIGN SHOWN THEREON IS THE PROPERTY OF ROJONE PTY LTD AND MUST NOT BE SOLD, LENT, GIVEN AWAY, COPIED, REPRODUCED OR OTHERWISE DIVULGED TO ANY THIRD PARTY OR USED FOR MANUFACTURE, OR ANY OTHER PURPOSE WITHOUT DIRECT WRITTEN PERMISSION OF ROJONE PTY LTD.

DO NOT SCALE

REVISION	DATE	CHECKED
A	2011-01-12	H. J.
B	2011-03-03	H. J.

UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES (mm) TOLERANCE: LINEAR ±0.1 ANGULAR ±1° REMOVE ALL BURRS AND SHARP EDGES

	ROJONE PTY LTD ACN 002691241 44 AERO RD INGLEBURN 2565 SYDNEY, AUSTRALIA Ph: (612) 9829 1555 Fax: (612) 9605 8812 Web: www.rojone.com.au E-mail: sales@rojone.com.au	TITLE INTERFACE FOR LNA WITH ALC AMA-3121	
	MATERIAL AS PART DRAWN Y. GU CHECKED H. JIA APPROVED		DRWG No: 003001001167
FINISH AS PART		SCALE 1:1	SHEET 1 OF 1
		FILENAME 003001001167ISSB.DWG	

A4