



SPEC

Frequency: 900MHz
 R/L: -15dB when mounted against metal
 Style: 1/2 wave dipole
 Temp: 65 °C Max.

Note:

Antenna designed to be mounted with one side against metal where no other mounting is available.

Part Number:

A-414-XXXXX

Cable length in centimeter.

Connector Style
ie: 17F

Female SMA
bulkhead Connector

0.3 meter STD Cable
Dia: Ø3mm

THIS DOCUMENT AND THE DESIGN SHOWN THEREON IS THE PROPERTY OF ROJONE PTY LTD AND MUST NOT BE SOLD, LENT, GIVEN AWAY, COPIED, REPRODUCED OR OTHERWISE DIVULGED TO ANY THIRD PARTY OR USED FOR MANUFACTURE, OR ANY OTHER PURPOSE WITHOUT DIRECT WRITTEN PERMISSION OF ROJONE PTY LTD.

REVISIONS

ISS	ZONE	DESCRIPTION/PER REQUEST	DATE	CHECK
A		FIRST ISSUE	04-02-2003	



ROJONE PTY LTD ACN 002691241
 61 AERO RD INGLEBURN 2565
 SYDNEY, AUSTRALIA
 Ph: (612) 9829 1555 Fax: (612) 9605 8812
 Web: www.rojone.com.au E-mail: sales@rojone.com.au

INTERFACE DOCUMENT

DRAWN	Y. GU
CHECKED	B. G.
APPROVED	B. G.

TITLE INTERFACE FOR GSM ANTENNA A-414-17F30	
DRWG No:	009001001151
SCALE 1:1	SHEET 1 OF 1
FILENAME 009001001151ISSA.DWG	A3