

[< Home](#)
[< Family](#)
[< Series](#)

SC6185
(SRL6185)

Aviation band antenna, 3 dBd gain, HD, 225-400 MHz

- Ideal for severe weather conditions at airports
- Single antenna model only
- Available with bird resistant cap and 3 ft. extension cable

Fabricated using lightweight rugged components to insure easy installation while providing superior resistance to harsh environmental conditions. These antennas provide reliable omnidirectional coverage.



www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1223 42 03 03	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 016345		SC6185	Issue: 76	Dated: 05-02-10 Dated: 12-12-95

Notes

*1 : 30 to 60 degrees

Electrical Specifications

Frequency Range	MHz	225 to 400	
Gain (nominal)	dBd (dBi)	2.9 (5)	
Input VSWR (max)		2.5:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Omni-directional	
Vertical beamwidth	degrees	30	*1
Average Power Input (max)	W	100	
Lightning protection		DC ground	
Bandwidth	MHz	175	
Electrical tilt (available)		2-6	


Mechanical Specifications

Connector		N (male)	
Width	in (mm)	4 (102)	
Depth	in (mm)	4 (102)	
Base pipe diameter	in (mm)	4 (102)	
Base pipe mounting length	in (mm)	10 (254)	
Weight	lbs (kg)	24.5 (11.1)	
Weight iced	lbs (kg)	39.5 (17.9)	
Actual Shipping weight	lbs (kg)	36 (16.3)	
Shipping dimensions	in (mm)	90x6x6 (2286x152x152)	
Length	in (mm)	76 (1930)	

Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)	
Wind Loading Area (Flat Plate Equivalent)	ft ² (m ²)	1.22 (0.11)	
Wind Loading Area (ice)	ft ² (m ²)	1.57 (0.15)	
Rated wind velocity (no ice)	mph (km/h)	275 (443)	
Rated wind velocity (1/2" radial ice)	mph (km/h)	225 (362)	
Lateral thrust (100mph)	lbs (N)	47 (209.1)	
Bending moment	ft-lbs (Nm)	144 (194.4)	
Tip deflection	degrees	0.1	

SINCLAIR TECHNOLOGIES



MEASURED RADIATION PATTERN
VERTICAL POLARIZATION

Elevation
Relative Gain - 10 dB per Division