



REVISIONS

ISS	ZONE	DESCRIPTION/PER REQUEST	DATE
B		updated spec	

3rd ANGLE PROJECTION

THIS DOCUMENT AND THE DESIGN SHOWN THEREON IS THE PROPERTY OF ROJONE PTY LTD AND MUST NOT BE SOLD, LENT, GIVEN AWAY, COPIED, REPRODUCED OR OTHERWISE DIVULGED TO ANY THIRD PARTY OR USED FOR MANUFACTURE, OR ANY OTHER PURPOSE WITHOUT DIRECT WRITTEN PERMISSION OF ROJONE PTY LTD.

DO NOT SCALE

REVISION	DATE	CHECKED
A	2010-03-30	Y. GU
B	2011-03-30	Y. GU

**SPECIFICATIONS
for AMA-1296-20-SF**

- Frequency Range:** 9.4 - 9.8 GHz
- Coupling (Port 1):** -20 dB ±1dB
- Coupling (Port 2):** -20 dB ±1dB
- Thru Loss:** < 0.7 dB
- VSWR:** < 1.5 : 1 (1.25 Typ)
- RF Input Power:** 50 Watts
- Impedance:** 50 Ohms
- Connector Type:** SMA - F
- Size:** 42x20x19 + conn.

ROJONE PTY LTD ACN 002691241 44 AERO RD INGLEBURN 2560 SYDNEY, AUSTRALIA Ph: (612) 9829 1555 Fax: (612) 9605 8812 Web: www.rojone.com.au E-mail: sales@rojone.com.au		TITLE INTERFACE DRAWING FOR AMA-1296-20-SF	
MATERIAL BRASS BODY		DRAWN Y. GU CHECKED	
FINISH PAINT		APPROVED H. JIA	
UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES (mm)		TOLERANCE: LINEAR ±0.1 ANGULAR ±1°	
REMOVE ALL BURRS AND SHARP EDGES		DRWG No: 001001250156	
		SCALE 1:1 SHEET 1 OF 1	
		FILENAME 001001250156ISSB.DWG	
		A4	

UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES (mm) TOLERANCE: LINEAR ±0.1 ANGULAR ±1° REMOVE ALL BURRS AND SHARP EDGES

