

Data Cables Multi-Pair Screened RS 422, RS 232

- Description:** • 7/0.20 (24 AWG) Tinned Copper, Polypropylene Insulated, Twisted Pairs, Aluminium / Mylar Tape Screened with a 7/0.20 mm Tinned Copper Drain Wire, PVC 4V-75 Sheathed
- Colour:** • Sheath: Grey
• Insulation: Chart A
- Pack Length:** • 100m and 500m Reels
- Operating Voltage:** • 300V RMS (non-mains)

Part No.	No. of Pairs	Insulation Thickness (mm)	Nominal Capacitance (PF/M)	Nominal Diameter (mm)	Approx. Weight (/100M)
ET 3001	1	0.3	68	4.0	1.8 Kg
ET 3002	2	0.3	50	5.3	3.5 Kg
ET 3003	3	0.3	50	6.2	4.1 Kg
ET 3004	4	0.3	50	6.8	5.3 Kg
ET 3005	5	0.3	50	7.6	6.5 Kg
ET 3006	6	0.3	50	8.4	7.7 Kg
ET 3008	8	0.3	50	9.4	9.4 Kg
ET 3012	12	0.3	50	11.0	12.4 Kg
ET 3018	18	0.3	50	13.3	17.5 Kg
ET 3025	25	0.3	50	15.4	23.3 Kg



High Speed Data Cable

Proudly one of Australia's top 100 Professional & Military Electronics, GPS, RF & Telecommunications companies