



< Family

www.sinctech.com

SVT- VHF

Mobile omni antenna

- · Rugged ABS housings are UV resistant
- · Stainless steel fittings
- · Stands up to severe environmental conditions

These antennas are fabricated from durable components and are designed to last. Fittings are constructed of stainless steel to inhibit rust and corrosion and are molded into the housing without the use of glue or fasteners to ensure a long lasting, reliable product, even in severe environments.

Many different mounts are available.

Application Notes

• Sinclair manufactures a wide range of mobile antennas. These products are very durable and reliable and can withstand the most severe environmental conditions. These antennas are suitable for public safety applications and other "mission critical" operations.

Model Description SVT-1180EX 0 dBd gain, 118-225 MHz SVT-1180SP 0 dBd gain, 118-512 MHz



Omni-directional

Pattern



Australian Representatives ROJONE, PTY LTD.

Tel: 02 9829 1555 E: sales@rojone.com.au www.rojone.com.au

United States Europe, Middle East and Africa Caribbean and Latin America Canada and rest of the world Region Canada: 1 800 263 3275 Telephone USA: 1 800 263 3275 International: +44 (0) 1223 42 03 03 International: +1 905 726 7676 International: +1 905 727 0165 E-mail salesusa@sinctech.com

Product Specification Sheet

salesuk@sinctech.com

SVT- VHF

salesla@sinctech.com

salescan@sinctech.com

Dated: 05-02-10

Bandwidth, MHz



Antennas Low Band, Aviation, and VHF Antennas **SVT-VHF Series**

SVT-1180EX SVT-1180SP

Electrical Specifications		
Frequency Range, MHz	118 to 225	118 to 512
Gain (nominal), dBd (dBi)	unity (2.1)	unity (2.1)
Input VSWR (max)	1.5:1	1.5:1
Polarization	vertical	vertical
Impedance, Ω	50	
Pattern		Omni-directional
Average Power Input (max), W	150	150

7.5

Mechanical Specifications			
Length/ Height, in (mm)	25 (635)	24 (610)	
Weight, lbs (kg)	0.5 (0.2)		
Shipping dimensions, in (mm)	Varies ()	Varies ()	

Environmental Specifications			
Temperature range, °F (°C)	-22 to +122 (-30 to +50)	-22 to +122 (-30 to +50)	

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1223 42 03 03	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		SVT- VHF		Dated: 05-02-10