



THIS DOCUMENT AND THE DESIGN SHOWN THEREON IS THE PROPERTY OF ROJONE PTY LTD AND MUST NOT BE SOLD, LENT, GIVEN AWAY, COPIED, REPRODUCED OR OTHERWISE DIVULGED TO ANY THIRD PARTY OR USED FOR MANUFACTURE, OR ANY OTHER PURPOSE WITHOUT DIRECT WRITTEN PERMISSION OF ROJONE PTY LTD.

DO NOT SCALE

REVISIONS		
ISS	ZONE	DESCRIPTION/PER REQUEST/DATE
A1		Add telstra serial no
B		Updated spec
C		UPDATED OVERALL SIZE

Telstra Serial No: 187/01513

SPECIFICATION for AMA-2257-8N	
Frequency Range:	690 to 2700 MHz
Isolation:	> 20 dB
Insertion Loss:	< 0.6 dB @ 900 MHz < 1 dB @ 1.9 GHz < 1.2 dB @ 2.5 GHz
PIM:	< -150 dBc @ 43dBm x2
Amplitude Balance:	< ± 0.3 dB
Return Loss:	-20dB Typ (-17dB Max.)
Max Power:	10 Watts @ VSWR 5:1
Impedance:	50 Ohms
Operating Temp:	-30 to +60 ° C
Connector:	N - F
Size:	254 x 150 x 19 mm excl Conn.
Weight:	Alum 2 Kg approx.

REVISION	DATE	CHECKED
A	2011-06-03	H. JIA
A1	2012-02-23	L. G.
B	2012-02-24	L. G.
C	2012-06-04	L. G.

		ROJONE PTY LTD ACN 002691241 44 AERO RD INGLEBURN 2565 SYDNEY, AUSTRALIA Ph: (612) 9829 1555 Fax: (612) 9605 8812 Web: www.rojone.com.au E-mail: sales@rojone.com.au		TITLE 8 WAY 690-2700MHz DIVIDER AMA-2257-8N INTERFACE DRAWING	
MATERIAL ALUMINIUM &/OR BRASS HOUSING & COVER		DRAWN Y. GU CHECKED L. G.		DRWG No: 002008250060	
FINISH PAINT		APPROVED		SCALE NTS SHEET 1 OF 1 FILENAME 002008250060issC.DWG	

ALL SPECIFICATIONS SUBJECT TO CHANGE UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES (mm) TOLERANCE: LINEAR ±0.1 ANGULAR ±1° REMOVE ALL BURRS AND SHARP EDGES

A4