


REVISIONS

ISS	ZONE	DESCRIPTION/PER REQUEST	DATE
A		First Issue - Obsolete	
B		Add Spec to issa drwing Released Livia 2014-03-20	

DRAWING STANDARD AS1100
3rd ANGLE
PROJECTION

THIS DOCUMENT AND THE DESIGN SHOWN THEREON IS THE PROPERTY OF ROJONE PTY LTD AND MUST NOT BE SOLD, LENT, GIVEN AWAY, COPIED, REPRODUCED OR OTHERWISE DIVULGED TO ANY THIRD PARTY OR USED FOR MANUFACTURE, OR ANY OTHER PURPOSE WITHOUT DIRECT WRITTEN PERMISSION OF ROJONE PTY LTD.


DO NOT SCALE




SPECIFICATION for AMA-2256-4N

- FREQUENCY BAND (MHz): 800-2500 MHz
- NUMBER OF WAYS: 4 Way
- ISOLATION (dB): > 20dB
- INSERTION LOSS (dB): 6.3 dB Type
- AMPLITUDE BALANCE (+/-dB): < +/-0.3 dB
- PHASE BALANCE (DEG): < +/- 10 Deg
- PEAK POWER (Watts): 1000 (Watts);
- PULSE WIDTH (µS): 10 (µS);
- AVERAGE POWER (Watts): 100 Watts
- IMPEDANCE (Ohms): 50
- VSWR: 1.22:1 Max
- MAXIMUM DIMENSIONS: 130 x 101 x 19 + Connector
- RF CONNECTOR TYPE: N - Female
- TEMPERATURE RANGE (Deg C): -40 to +85

REVISION	DATE	CHECKED
A	2004-04-06	H. J.
B	2014-03-20	L. B.



 <p>ROJONE PTY LTD ACN 002691241 44 AERO RD INGLEBURN 2565 SYDNEY, AUSTRALIA</p> <p>Ph: (612) 9829 1555 Fax: (612) 9605 8812 Web: www.rojone.com.au E-mail: sales@rojone.com.au</p>	<p>TITLE INTERFACE DRAWING FOR AMA-2256-4N 4 WAY DIVIDER</p>	
	<p>DRWG No: 002004250043</p>	
<p>MATERIAL ALUMINIUM ALLOY 6061 BODY</p>	<p>DRAWN Y. GU</p>	<p>SCALE NTS</p>
<p>FINISH POLYURETHANE AS2700 N42 STORM GREY</p>	<p>CHECKED L. B.</p>	<p>SHEET 1 OF 1</p>
<p>APPROVED L. B.</p>		<p>FILENAME 002004250043ISSB.DWG</p>

UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES (mm) TOLERANCE: LINEAR +0.1 ANGULAR +1° REMOVE ALL BURRS AND SHARP EDGES

A4