



## Cable Ties

(Model: HE Series - See Table below)



### Specifications

#### Plastic Cable Ties

PART NUMBER	LENGTH	WIDTH	MATERIAL	TEMPERATURE	FLAMMABILITY
HE-T18RW	100 mm	2.5 mm	PA66	-40°C to 85°C continuous. 105°C for 500 hours	UL94 V2
HE-T50RW	200 mm	4.6 mm	PA66	-40°C to 85°C continuous. 105°C for 500 hours	UL94 V2
HE-T30LL-W	290 mm	3.5 mm	PA66	-40°C to 85°C continuous. 105°C for 500 hours	UL94 V2
HE-T50IW	300 mm	4.6 mm	PA66	-40°C to 85°C continuous. 105°C for 500 hours	UL94 V2
HE-T120I-BLK	300 mm	7.6 mm	PA66	-40°C to 85°C continuous. 105°C for 500 hours	UL94 V2
HE-T50LW	390 mm	4.6 mm	PA66	-40°C to 85°C continuous. 105°C for 500 hours	UL94 V2

#### Material Properties, PA66

- ❖ High Yield Strength

#### Stainless Steel Cable Ties

PART NUMBER	LENGTH	WIDTH	MATERIAL	TEMPERATURE	FLAMMABILITY
HE-STB-200S	200 mm	4.5 mm	316 grade stainless steel	-80°C to 538°C	N/A
HE-MBT8HFC	201 mm	7.9 mm	316 grade stainless steel	-80°C to 538°C	N/A
HE-STB-360	360 mm	4.5 mm	316 grade stainless steel	-80°C to 538°C	N/A
HE-STB-360M	360 mm	8 mm	316 grade stainless steel	-80°C to 538°C	N/A
HE-MBT14HFC	362 mm	7.9 mm	316 grade stainless steel	-80°C to 538°C	N/A

#### Material Properties, 316 Grade Stainless Steel

- ❖ Salt spray resistant
- ❖ Corrosion resistant
- ❖ Weather resistant
- ❖ Outstanding chemical resistance
- ❖ Anti-magnetic

