Australian Representatives
ROJONE, PTY LTD.
Tel: 02 9829 1555
E: sales@rojone.com.au
www.rojone.com.au

I. CONSTRUCTION

	DIAMETER
Center conductor: Solid Bare Copper	.044 “
Dielectric: Gas Injected Foam Polyethylene	.116 “
Shield: Bonded Aluminum-Polyester-Aluminum Tape	.121”
: 36 GA Tinned Copper Braid (90%k)	.144”
Jacket: Black Low Smoke Low Toxicity Non-halogen FR Polyethylene	.195” +/-.010”

II. ENVIRONMENTAL and MECHANICAL PROPERTIES

Weight: 28 pounds per 1000 feet
Operating temperature: -40°C to +85°C
Minimum bend radius: 1/2 inch
Flame & smoke: **SEE NOTES BELOW**

III. ELECTRICAL PROPERTIES

Impedance: 50 ohms
Capacitance: 24.5 pF per foot
Velocity: 83 %
Dc resistance (center conductor): 5.36 ohms per 1000 feet
(Outer conductor): 4.90 ohms per 1000 feet

Attenuation @ Typical (max)	
30 MHz:	1.8 dB per 100 feet
50 MHz:	2.3 dB per 100 feet
150 MHz:	4.0 dB per 100 feet
220 MHz:	4.8 dB per 100 feet
450 MHz:	7.0 dB per 100 feet
900 MHz:	9.9 dB per 100 feet
1500 MHz:	12.9 dB per 100 feet
2000 MHz:	15.0 dB per 100 feet
2500 MHz:	16.9 dB per 100 feet

Shielding: >90dB

IV. NOTES

1. Flame: Meets IEC-332-1-2, IEC 332-3 CAT.C, UL-VW1, UL-1581, IEE-383, BS-4066-1, BS-4066-3
2. Smoke: Meets IEC-61034-2, NES-711
3. Halogen: Meets IEC-60754-1, BS 6425-1, IEC-60754-2, BS 6425-2
4. MISC: Compliant to EN-45545 (R15/R16), DIN 5510-2, NF F16-101, BS-6853 Standards
5. UV Resistant: Meets UL-1581, 720 Hour UV Exposure
6. Meets NFPA-130 Requirements
7. ROHS Compliant: 2002/95/EC ROHS Directive and Amendment 2011/65/EC

This document contains Times Microwave Systems proprietary information. It shall not be duplicated, used or disclosed in whole or in part to third parties without written authorization from Times Microwave Systems. This data is EAR controlled IAW 15 CFR Part 730-774

Approvals		
Drawn	EP	5/4/2016
CHK	TF	5/4/2016

This Technical Specification is for Reference only

TIMES MICROWAVE SYSTEMS
Wallingford, CT 06492
(203) 949-8400; (203) 949-8423.Fax

LMR-200-LSZH

Size	CAGE CODE	Drawing No.:
A	**68999**	**AA-11762**

Scale: NA	Rev. (--B)	Sheet: 1 of 1